




NTN Bearing Driveshaft do Brasil



skf SSAFS 22536 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22536 T

SSAFS 22536 T Bearing 2D drawings and 3D CAD models

d_a	163.512 mm
D_a	319.999 mm
C_a	95.809 mm
A_1	180.975 mm
A_2	314.325 mm
S	4.763 mm
b_a	75.406 mm
H	377.825 mm
H_1	190.5 mm
H_2	76.2 mm
L	679.45 mm
R_1	114.3 mm
R_2	41.275 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	60.325 mm
Housing	SSAFS 536
Bearing	22236 CCK/W33
Adapter sleeve assembly	SNW 36x6.7/16
Stabilizing ring	SR-36-30
Taconite seal	TER 148
End plug (suffix Y)	EPR 19
Max. speed for Taconite seal	460 r/min
P_{60°	535 kN
P_{90°	320 kN



NTN Bearing Driveshaft do Brasil

P_{120°	196 kN
P_{150°	173 kN
P_{180°	202 kN
P_a	46.3 kN
Mass pillow block	197 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	1304.1 g