



NTN Bearing Driveshaft do Brasil

65 mm x 90 mm x 17 mm NTN 4T-32913XST
Single row tapered roller bearings

Bearing No. 4T-32913XST

d	65 mm
D	90 mm
B	17 mm
C	14 mm
T	17 mm
d1	78 mm
a	16.5 mm
rs min	1 mm
r1s min	1 mm
e	0.35
Y2	1.7
Y0	0.93
Mass	0.32 kg
ISO 355 reference	T2BC065
Dynamic load, C	48.5 kN
Rating life coefficient, A2	1.4
Static load, C0	85 kN
Fatigue limit load, Cu	10.4 kN
Nlim (oil)	4,900 rpm
Nlim (grease)	3,700 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.47 Hz

4T-32913XST Bearing 2D drawings and 3D CAD models



NTN Bearing Driveshaft do Brasil

Characteristic rolling element frequency, BSF	14.74 Hz
Characteristic outer ring frequency, BPF0	17.28 Hz
Characteristic inner ring frequency, BPF1	19.72 Hz
da max	70 mm
db min	70.5 mm
Da min	80 mm
Da max	84.5 mm
Db min	86.5 mm
Ca min	3 mm
Cb min	3 mm
ra max	1 mm
r1a max	1 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.31
Product Group	B04334